

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CELEROL-Touch up Paint 929-77 11C6 Currygelb seidenglänzend

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Industrial serial painting

1.3 Details of the supplier of the safety data sheet

Producer : Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:

Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone : +49 (0) 40 75103 0
Telefax : +49 (0) 40 75103 375
E-mail address of person responsible for the SDS : sdb_info@umco.de

1.4 Emergency telephone number

Emergency telephone number : +44 1235 239670 (Carechem International)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

xylene

Additional Labelling

EUH208 Contains 1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine, dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins, pigments, organic solvents and propellant

Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

	EC-No. Index-No. Registration number		(% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 12.5 - < 20
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 12.5
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 5
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2.5
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 5
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine	54914-37-3 259-393-4 01-2119978283-28	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	< 0.1
dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7 273-028-6 01-2120770324-57	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 3; H412	>= 0.0025 - < 0.025
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6	Flam. Gas 1A; H220	>= 25 - < 40

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank
Ort
Hamburg
Hamburg
Hamburg
Kto.-Nr.
600227300
59273300
373205
BLZ

BIC
DEUTDE33
HYVEDE33
PBNDDE33
IBAN
200 700 00 DEUTDE33
200 300 00 HYVEDE33
200 100 20 PBNDDE33

DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

	204-065-8 603-019-00-8 01-2119472128-37	Press. Gas Compr. Gas; H280	
--	---	--------------------------------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank

Ort
Hamburg
Hamburg
Hamburg

Kto.-Nr.
600227300
59273300
373205

BLZ
200 700 00
200 300 00
200 100 20

BIC
DEUTDE33HAN
HYVEDE33HAN
PBNDDE33HAN

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

Exposure to heat may cause bursting of the aerosol packagings.

5.3 Advice for firefighters

- Special protective equipment : Appropriate breathing apparatus may be required.
for firefighters
- Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO
ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

- Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform
appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent
materials, e.g. sand, earth, vermiculite, diatomaceous earth
and place in container for disposal according to local regula-
tions (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Prevent the creation of flammable or explosive concentrations
of vapour in air and avoid vapour concentrations higher than
the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the ap-
plication area.
Observe specific national regulations for handling and use of
paints.
- Advice on protection against fire and explosion : The product should only be used in areas from which all na-
ked lights and other sources of ignition have been excluded.
Preparation may charge electrostatically: always use earthing
leads when transferring from one container to another. Opera-



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

tors should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Storage rooms must be properly ventilated.
- Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

- Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1,000 ppm 1,920 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	400 ppm 766 mg/m3	GB EH40
		STEL	500 ppm 958 mg/m3	GB EH40
acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	500 ppm 1,210 mg/m3	GB EH40
		STEL	1,500 ppm 3,620 mg/m3	GB EH40
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the			



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

	skin, Indicative			
		TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/E U
	Further information: Indicative			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	125 ppm 552 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

		STEL	100 ppm 548 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
dimethylbis[(1-ox-oneodecyl)oxy]stannane	68928-76-7	TWA	0.1 mg/m3 (Tin)	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	0.2 mg/m3 (Tin)	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m3
	Consumers	Inhalation	Long-term systemic effects	471 mg/m3
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Dermal	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Consumers	Dermal	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	62 mg/kg bw/day
xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Dermal	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m3
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12.5 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic	300 mg/m3

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank
Ort
Hamburg
Hamburg
Hamburg
Kto.-Nr.
600227300
59273300
373205
BLZ
200 700 00
200 300 00
200 100 20
BIC
DEUTDE33
HYVEDE33
PNKDEFF200
IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

			effects	
	Workers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
ethyl 3-ethoxypropionate	Workers	Skin contact	Long-term systemic effects	102 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	610 mg/m3
	Consumers	Inhalation	Long-term systemic effects	72.6 mg/m3
	Consumers	Oral	Long-term systemic effects	1.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	24.2 mg/kg bw/day
ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15 mg/m3
	Consumers	Oral	Long-term systemic effects	1.6 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Consumers	Oral	Long-term systemic effects	0.526 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0.155 mg/l
	Marine water	0.016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0.681 mg/kg dry weight (d.w.)

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank
Ort
Hamburg
Hamburg
Hamburg
Kto.-Nr.
600227300
59273300
373205
BLZ
200 700 00
200 300 00
200 100 20
BIC
DEUTDE33
HYVEDE33
PBNDDE33
IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

	Marine sediment	0.069 mg/kg dry weight (d.w.)
	Soil	0.045 mg/kg dry weight (d.w.)
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Fresh water sediment	30.4 mg/kg dry weight (d.w.)
	Marine sediment	3.04 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Soil	29.5 mg/kg dry weight (d.w.)
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Soil	2.31 mg/kg dry weight (d.w.)
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.0018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Soil	0.09 mg/kg dry weight (d.w.)
ethyl 3-ethoxypropionate	Fresh water	0.061 mg/l
	Marine water	0.006 mg/l
	Sewage treatment plant	50 mg/l
	Fresh water sediment	0.419 mg/kg dry weight (d.w.)
	Marine sediment	0.042 mg/kg dry weight (d.w.)
	Soil	0.048 mg/kg dry weight (d.w.)
ethylbenzene	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Fresh water sediment	13.7 mg/kg dry weight (d.w.)
	Marine sediment	1.37 mg/kg dry weight (d.w.)
	Sewage treatment plant	9.6 mg/l
	Soil	2.68 mg/kg dry weight (d.w.)
2-methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l
	Marine water	0.064 mg/l
	Fresh water sediment	3.29 mg/kg dry weight (d.w.)

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank
Ort
Hamburg
Hamburg
Hamburg
Kto.-Nr.
600227300
59273300
373205

BLZ
200 700 00
200 300 00
200 100 20
BIC
DEUTDE33
HYVEDE33
PBNDDE33

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

	Marine sediment	0.329 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Soil	0.29 mg/kg dry weight (d.w.)
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine	Fresh water	0.015 mg/l
	Marine water	0.001 mg/l
	Sewage treatment plant	3.04 mg/l

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

- Respiratory protection** : If the solvent concentration is above the air limit values, a breathing apparatus approved for this purpose must be worn. Use half-mask model with cartridge or air-fed. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapour. If possible, machine employing a wet medium. Where practicable, install exhaust hoods to improve capture of vapours and fumes and avoid exposition; otherwise wear respiratory protection equipment.
- Protective measures** : Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state** : aerosol
- Colour** : according product name
- Odour** : characteristic
- Boiling point/boiling range** : < 35 °C
- Flash point** : -42 °C
Method: ISO 13736
- Auto-ignition temperature** : ca. 240 °C
- pH** :
No data available
- Viscosity**
Viscosity, kinematic : > 6 mm²s
- Flow time** : 12 s
Cross section: 4 mm
Method: DIN 53211

< 10 s
Cross section: 6 mm
Method: ISO 2431

Solubility(ies)

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name
Deutsche Bank
HypoVereinsbank
Postbank

Ort
Hamburg
Hamburg
Hamburg

Kto.-Nr.
600227300
59273300
373205

BLZ
200 700 00
200 300 00
200 100 20

BIC
DEUTDE33HAN
HYVEDE33HAN
PBNDDE33HAN

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

Water solubility : insoluble

Vapour pressure : ca. 5,000 hPa (50 °C)

Density : 1.21 g/cm³ (20 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg

dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 892 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : irritating

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

allergic contact dermatitis and absorption through the skin.
Inhalation of aerosol may cause irritation to the upper respiratory tract.
Inhalation of aerosols may cause irritation to mucous membranes.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

- ADR : UN 1950
- IMDG : UN 1950
- IATA : UN 1950

14.2 UN proper shipping name

- ADR : AEROSOLS, FLAMMABLE
- IMDG : AEROSOLS
- IATA : AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|------|-------|------------------|
| ADR | : 2 | 2.1 |
| IMDG | : 2 | 2.1 |
| IATA | : 2.1 | |

14.4 Packing group

- ADR
- Packing group : Not assigned by regulation
- Classification Code : 5F
- Labels : 2.1
- Tunnel restriction code : (D)
- Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG

- Packing group : Not assigned by regulation
- Labels : 2.1
- EmS Code : F-D, S-U

IATA (Cargo)

- Packing instruction (cargo aircraft) : 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: 68928-76-7 (Number on list 20)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 77.5 %, 938 g/l
VOC content excluding water

Other regulations:

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-Touch up Paint 929-77
Quality No.: 9297711C67000

Revision Date 08.11.2022
Print Date 08.11.2022
Version 2

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

